

CICIND

Model Code for Steel Chimneys

REVISION 1 – 1999

TABLE OF CONTENTS

Foreword	3	7.2.3.3 Effect of fluctuating part of the wind-speed	8
0 Introduction	3	7.2.4 Vortex shedding	8
0.1 General	3	7.2.4.1 General principles	8
0.2 Appendices and Commentaries	3	7.2.4.2 Estimation of top amplitudes	9
0.3 Philosophy	3	7.2.4.3 Bending Moments due to vortex shedding	9
1 Scope	3	7.2.5 Ovalling	9
2 Field of Application	3	7.2.5.1 Static effects	9
3 References	3	7.2.5.2 Dynamic effects	10
4 Notations, Units and Definitions	4	7.2.6 The increase of wind effects by nearby structures	10
4.1 General	4	7.2.6.1 Increase in along-wind load	10
4.2 Subscripts-Superscripts	4	7.2.6.2 Increase in cross-wind response	10
4.3 Units	4	7.2.7 Damping ratio	11
4.4 Definitions	4	7.2.8 The first and second natural frequencies	11
5 Basis of Design and Safety Factors	4	7.2.9 Passive dynamic control	11
5.1 General	4	7.2.9.1 Aerodynamic stabilisers	11
5.2 Reliability differentiation	4	7.2.9.2 Damping devices	11
5.3 Partial Safety Factors	5	7.2.9.3 Special chimney designs for damping	12
5.4 Cross-wind effects	5	7.3 Earthquake loading	12
6 Materials	5	7.4 Thermal effects	12
6.1 General	5	7.5 Explosions	12
6.2 Structural steels	5	7.5.1 External explosions	12
6.3 Stainless and alloy steels	6	7.5.2 Internal explosions	12
7 Actions (External and Internal)	6	7.6 Internal effects governing the chimney design	12
7.1 Permanent Load	6	7.6.1 High temperature flue gases	12
7.1.1 Dust load (temporary load)	6	7.6.2 Fire	12
7.2 Wind	6	7.6.3 Chemical effects	12
7.2.1 General	6	8 Design of Structural Shell	13
7.2.2 Wind Speed	6	8.1 Minimum thickness	13
7.2.2.1 Basic wind speed	6	8.2 Required checks	13
7.2.2.2 Design wind speed	7	8.3 Carrying capacity of shell	13
7.2.2.3 The influence of topography	7		
7.2.3 Wind load in direction of the wind	8		
7.2.3.1 Wind load on isolated chimneys	8		
7.2.3.2 Mean hourly wind load	8		

DISCLAIMER

This CICIND Model Code is presented to the best of the knowledge of its members as a guide only. CICIND is not, nor are any of its members, to be held responsible for any failure alleged or proved to be due to adherence to recommendations or acceptance of information published by the association in a Model Code or in any other way.

Extracts from standards are reproduced with the permission of BSI under licence number PD\1999 1591.

Complete copies of the standard can be obtained by post from BSI Customer Services, 389 Chiswick High Road, London W4 4AL, UK

CICIND, Talacker 50, CH-8001, Zurich, Switzerland

Copyright by CICIND, Zurich

8.3.1	Load factors and load combinations	13	9.2	Flanged connections	21
8.3.2	Second order effects	13	9.3	The support at the base	21
8.3.3	Biaxial stresses	13	9.3.1	Anchor bolts	21
8.3.4	Stability	13	9.3.2	Grouting	21
8.4	Serviceability of shell	14	9.3.3	Temperature effects	21
8.5	Fatigue check	14	10	Steel liners	21
8.5.1	Basic principles	14	11	Construction	21
8.5.2	Fatigue strength	14	11.1	General	21
8.5.3	Influence of high temperature	14	11.2	Structural shell	21
8.6	Allowance for corrosion	14	11.3	Structural flanges and opening reinforcement	22
8.6.1	External corrosion allowance	19	11.4	Stiffening rings	22
8.6.2	Internal corrosion allowance	19	11.5	Base plate	22
9	Design Details	19	11.6	Straightness	22
9.1	Connections	19	11.7	Erection tolerance	22
9.1.1	General provisions	19	12	Surface Protection	22
9.1.2	Bolted connections	19	13	Openings	22
9.1.2.1	Shear	19	14	Guyed and Stayed Chimneys	22
9.1.2.2	Bearing on connected surfaces	19	14.1	Stayed chimneys	22
9.1.2.3	Tension	19	14.2	Guyed chimneys	22
9.1.2.4	Combined loading	20	15	Protection Against Lightning	22
9.1.2.5	Deduction for holes	20	16	Access Ladders	22
9.1.3	Welded connections	20	17	Aircraft Warning Lights	22
9.1.3.1	Full penetration welds	20			
9.1.3.2	Fillet welds	20			
9.1.3.3	Weld testing	21			